

AQUENCE®**AQUENCE CG 1556**Formerly known as
ULTIMATE CONTROL® 33-1556

August 2012

TYPE:

Formulated Polyvinyl Resin Emulsion

PHYSICAL PROPERTIES:

Appearance: Thin, white fluid

Solids: Approx. 57.5%

Viscosity: Approx. 2,500 cps.

pH: Approx. 4.1

Lbs./Gallon: Approx. 9.0

SUGGESTED USES:

Envelope back seam gum for hard to adhere surfaces such as Du Pont Tyvek(R).

This product is compliant with FDA 175.105. To the best of our knowledge, after review of the formulations, this product does not contain any wheat, barley or rye gluten. The information being provided regarding the substances contained in this product comes from reviewing information provided by suppliers or producers of the raw materials used in this product. We have not conducted any tests to determine the actual amount of these substances in the above product.

OPERATING CONDITIONS:

1. Applied from glue roll or stencil.
2. Supplied ready-for-use, but may be diluted with water if necessary.
3. Clean-up: Wet film with water. Dry film with 50/50 acetone/water mixture.

PRECAUTIONS:

Protect from temperatures below 40°F. Rotate stock using oldest material first. Keep covered to prevent drying out and contamination. Do not mix with other adhesives.

Note

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage

Except as otherwise noted, all marks used are trademarks of Henkel or its affiliates in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Henkel Corporation

Tel: 1.888.480.6889

Email: bw.nacustomerservice@henkel.com

www.henkelna.com

