



Technical Data Sheet  
**AQUENCE FB 711C**  
**VELOCITY**

Formerly known as  
**VELOCITY® 33-711C**

September 2012

**TYPE:**

Formulated Emulsion Adhesive

**PHYSICAL PROPERTIES:**

Appearance: Fluid white product, UV Indicator

Solids: Approx. 54%

Viscosity: Approx. 5,500 cps

pH: Approx. 4.5

Lbs./Gallon: Approx. 9.1

**SUGGESTED USES:**

Clean machining product for wheel and bottom pot applications. Machining properties include good stability, ideal transfer and good cut-off. Use for Folding Carton and Glued Lap applications. Excellent adhesion properties to un-coated cartons; above average heat and cold resistance. Meets composition requirements of Indirect Food Additives Regulation 21 CFR 175.105 "Adhesives".

**OPERATING CONDITIONS:**

Non-contact Extrusion

1. Stir thoroughly before using.
2. Ready-for-use viscosity as supplied. May be diluted with water if desired.
3. Wet and dry film soluble in warm water.

**PRECAUTIONS:**

Protect from temperatures below 40° F. Rotate stock using oldest material first. Keep covered to prevent drying out and contamination. Do not mix with other adhesives.

**Note**

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

**Trademark usage**

Except as otherwise noted, all marks used are trademarks of Henkel or its affiliates in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

**Henkel Corporation**

Tel: 1.888.480.6889

Email: [bw.nacustomerservice@henkel.com](mailto:bw.nacustomerservice@henkel.com)

[www.henkelna.com](http://www.henkelna.com)

