

DESCRIPTION

Aquence Bottle Labeling

FIELD OF APPLICATION

Labeling

TECHNICAL DATA

Viscosity	85,000cps. @76°F Brookfield RVF, #7@20
pH	8.6
Density	9.0lbs/gallon
Color	Translucent
Solids	52%

PROPERTIES

Aquence XP 77 is synthetic polymer labeling glue. This product exhibits high wet tack, with fast speed of set, and extremely clean machining. AquenceXP 77 is formulated to have very easy clean up, while offering excellent adhesion to PET and over-coated low dyne glass. This product is also formulated to have good Hyper-condensation resistance for use on wet bottles. All ingredients in Aquence XP 77 are approved under the Federal Regulation 21 CFR 175.105, which relates to incidental contact of adhesives with food.

HANDLING AND APPLICATION:

Aquence XP 77 is supplied ready for use. Preferred running temperature is 70-85°F. Clean up wet or dry adhesive with water.

PRECAUTIONS:

Avoid skin and eye contact. Do not mix with other adhesives.

STORAGE CONDITIONS:

Keep from freezing. Container should be covered when not in use to prevent moisture loss and contamination. Shelf life is 6 months.

Note

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage

Except as otherwise noted, all marks used are trademarks of Henkel or its affiliates in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.